



Features:

- Shrink Ratio: 3:1
- Operating temperature: -45°C to + 125°C
- Approvals: UL 224 125°C 600 File E204071
- Minimum fully recovery temperature: 110°C
- RosHS compliant
- Voltage rating : 600V
- Flame retardant VW-1

REF	TRTA3-M-019	TRTA3-M-025	TRTA3-M-033	TRTA3-M-040	TRTA3-M-055	TRTA3-M-065	TRTA3-M-075	TRTA3-M-100
ØA (as supplied)	19	25	33	40	55	65	75	100
ØB (after recovered)	6	8	8	12	16	19	22	30

TOL GEN.DIN 7168	>0.5 a 6	>6 a 30	>30 a 120	>120 a 315	>315 a 1000	>1000 a 2000	Angles ± 0.5	Version	Sheet size	Drawn	TRTA3-M		Material	Color	Finish
	± 0.05	± 0.1	± 0.15	± 0.2	± 0.3	± 0.5		R04	A3				Part name	Project	Poliolfine
	□ FIND	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8		± 1.2	Sheet number	Checked	Date	SHRINKABLE CABLE PROTECTION	CABLE PROTECTION	This drawing contains confidential information. Not allowed its reproduction total or partial All dimensions in metric system	
□ MEDIO	± 0.2	± 0.5	± 0.8	± 1.2	± 2	± 3	1/1	-	11/06/19						
□ BASTO															

