



Features:

Shrink Ratio: 6:1

Operating temperature : -55°C to 110°C

Heavy Wall Tubing with Hot Melting Adhesive

Resistant to UV-radiation

High electrical insulation

Superior mechanical property

Minimum fully recovery temperature: 120° C

Voltage rating: 600V

REF	TRTA6-019	TRTA6-033	TRTA6-044.4	TRTA6-050.8	TRTA6-069.8	TRTA6-088.9	TRTA6-119.4	TRTA6-235.0
ØA (as supplied)	19	33	44.4	50.8	69.8	88.9	119.4	235
ØB (after recovered)	3.2	5.5	7.4	8.3	11.7	17.1	22.9	40
L	1000-1220	1000-1220	1000-1220	1000-1220	1000-1220	1000-1220	1000-1220	1000

TOL. GEN. DIN 7168	>0.5	>6	>30	>120	>315	>1000	Angles ± 0.5	Version	Sheet size	Drawn	TRTA6		Material	Color	Finish
	$\frac{a}{6}$	$\frac{a}{30}$	$\frac{a}{120}$	$\frac{a}{315}$	$\frac{a}{1000}$	$\frac{a}{2000}$		R04	A3		Part name	Project	Poliolfine	Black	Flat
<input type="checkbox"/> FIND	± 0.05	± 0.1	± 0.15	± 0.2	± 0.3	± 0.5		Sheet number	Checked	Date	SHRINKABLE CABLE	CABLE PROTECTION	This drawing contains confidential information. Not allowed its reproduction total or partial All dimensions in metric system		
<input type="checkbox"/> MEDIO	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2		1/1	-	11/06/19	PROTECTION				
<input type="checkbox"/> BASTO	± 0.2	± 0.5	± 0.8	± 1.2	± 2	± 3									

