

**Features:**

Shrink Ratio: 2.1

Operating temperature: -45°C to + 125°C

Approvals: UL 224 E204071

Minimum fully recovery temperature: 110°C


RosHS compliant

Voltage rating : 600V

Flame retardant VW-1



REF	TRTA-6.4	TRTA-38.1
ØA (as supplied)	6.4	38.1
ØB (after recovered)	3.2	19

TDL_GEN.DIN 7168	>0.5 a 6	>6 a 30	>30 a 120	>120 a 315	>315 a 1000	>1000 a 2000	Angles <b>± 0.5</b>	Version	Sheet size	Drawn	TRTA		Material	Color	Finish	
	± 0.05	± 0.1	± 0.15	± 0.2	± 0.3	± 0.5		R04	A3		Part name	Project	Poliolfine	Black	Flat	
	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2		Sheet number	Checked	Date	SHRINKABLE CABLE PROTECTION	CABLE PROTECTION	This drawing contains confidential information. Not allowed its reproduction total or partial All dimensions in metric system			
± 0.2	± 0.5	± 0.8	± 1.2	± 2	± 3											
<input type="checkbox"/> FIND								1/1	-	07/06/19						
<input type="checkbox"/> MEDIO																
<input type="checkbox"/> BASTO																

