



HOLE : Ø4.0
THICKNESS: 0.8-2.0



| | | | | | | | | | | | | | | | |
|--------------------------------|----------------|---------------|-----------------|------------------|-------------------|--------------------|-----------------|--------------|------------|----------|----------------|------------|---|---------------|--------|
| TOL. GEN. DIN 7168 | >0.5 a 6 | >6 a 30 | >30 a 120 | >120 a 315 | >315 a 1000 | >1000 a 2000 | Angles ± 0.5 | Version | Sheet size | Drawn | FAQF | | Material | Color | Finish |
| | ± 0.05 | ± 0.1 | ± 0.15 | ± 0.2 | ± 0.3 | ± 0.5 | | R04 | A3 | | Part name | Project | Nylon 66 (UL 94V-2) | Natural/Black | |
| <input type="checkbox"/> FIND | ± 0.05 | ± 0.1 | ± 0.15 | ± 0.2 | ± 0.3 | ± 0.5 | | Sheet number | Checked | Date | ANCHOR SUPPORT | WIRE MOUNT | This drawing contains confidential information. Not allowed its reproduction total or partial All dimensions in metric system | | |
| <input type="checkbox"/> MEDIO | ± 0.1 | ± 0.2 | ± 0.3 | ± 0.5 | ± 0.8 | ± 1.2 | | 1/1 | - | 08/07/19 | | | | | |
| <input type="checkbox"/> BASTO | ± 0.2 | ± 0.5 | ± 0.8 | ± 1.2 | ± 2 | ± 3 | | | | | | | | | |

